







NVR recorders

Artikelnummer	40101	40102	40103	40104
Model	DS-7608NI-K2/8P	DS-7608NI-K2	DS-7616NI-K2	DS-7616NI-K2/16P
				
Aantal kanalen	8	8	16	16
Bandbreedte (inkomend)	80 Mbps	80 Mbps	160 Mbps	160 Mbps
Bandbreedte (uitgaand)	160 Mbps	160 Mbps	160 Mbps	160 Mbps
HDMI Output	4K (3840 × 2160)/30Hz, 2K (2560 × 1440)/60Hz, 1920 × 1080/60Hz, 1600 × 1200/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz, 1024 × 768/60Hz	4K (3840 × 2160)/30Hz, 2K (2560 × 1440)/60Hz, 1920 × 1080/60Hz, 1600 × 1200/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz, 1024 × 768/60Hz	4K (3840 × 2160)/30Hz, 2K (2560 × 1440)/60Hz, 1920 × 1080/60Hz, 1600 × 1200/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz, 1024 × 768/60Hz	4K (3840 × 2160)/30Hz, 2K (2560 × 1440)/60Hz, 1920 × 1080/60Hz, 1600 × 1200/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz, 1024 × 768/60Hz
Decoding	H.265/H.265+/H.264/H.264+/MPEG4	H.265/H.265+/H.264/H.264+/MPEG4	H.265/H.265+/H.264/H.264+/MPEG4	H.265/H.265+/H.264/H.264+/MPEG4
SATA	2 harddisk bays	2 harddisk bays	2 harddisk bays	2 harddisk bays
Capaciteit	Maximaal 8 TB per harddisk	Maximaal 8 TB per harddisk	Maximaal 8 TB per harddisk	Maximaal 8 TB per harddisk
Alarm In/Uit	4/1	4/1	4/1	4/1
Netwerk Interface	1 RJ-45 10/100/1000 Mbps self-adaptive Ethernet interface	1, RJ-45 10/100/1000 Mbps self-adaptive Ethernet interface	1, RJ-45 10/100/1000 Mbps self-adaptive Ethernet interface	1, RJ-45 10/100/1000 Mbps self-adaptive Ethernet interface
PoE Interface	8, RJ-45 10/100 Mbps self-adaptive Ethernet interface	-	-	16, RJ-45 10/100 Mbps self-adaptive Ethernet interface
USB Interface	Voorzijde: 1 × USB 2.0; Achterzijde: 1 × USB 3.0	Voorzijde: 1 × USB 2.0; Achterzijde: 1 × USB 3.0	Voorzijde: 1 × USB 2.0; Achterzijde: 1 × USB 3.0	Voorzijde: 1 × USB 2.0; Achterzijde: 1 × USB 3.0



Artikelnummer	40105	40200	40503	40400
Model	DS-7616NI-I2	DS-7716NI-I4(B)	DS-7732NI-I4	DS-7716NI-I4/16P
				
Aantal kanalen	16	16	16	16
Bandbreedte (inkomend)	160 Mbps	160 Mbps	256 Mbps	160 Mbps
Bandbreedte (uitgaand)	256 Mbps	256 Mbps	256 Mbps	256 Mbps
HDMI Output	4K (3840 × 2160)/60Hz, 4K (3840 × 2160)/30Hz, 1920 × 1080/60Hz, 1600 × 1200/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz, 1024 × 768/60Hz	4K (3840 × 2160)/60Hz, 4K (3840 × 2160)/30Hz, 1920 × 1080/60Hz, 1600 × 1200/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz, 1024 × 768/60Hz	4K (3840 × 2160)/60Hz, 4K (3840 × 2160)/30Hz, 1920 × 1080/60Hz, 1600 × 1200/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz, 1024 × 768/60Hz	4K (3840 × 2160)/60Hz, 4K (3840 × 2160)/30Hz, 1920 × 1080/60Hz, 1600 × 1200/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz, 1024 × 768/60Hz
Decoding	H.265/H.265+/H.264/H.264+/MPEG4	H.265/H.265+/H.264/H.264+/MPEG4	H.265/H.265+/H.264/H.264+/MPEG4	H.265/H.265+/H.264/H.264+/MPEG4
SATA	2 harddisk bays	4 harddisk bays	4 harddisk bays	4 harddisk bays
Capaciteit	Maximaal 10 TB per harddisk	Maximaal 10 TB per harddisk	Maximaal 10 TB per harddisk	Maximaal 10 TB per harddisk
Alarm In/Uit	4/1	16/4	16/4	16/4
Netwerk Interface	1 RJ-45 10/100/1000 Mbps self-adaptive Ethernet interface	2 RJ-45 10/100/1000 Mbps self-adaptive Ethernet interfaces	2 RJ-45 10/100/1000 Mbps self-adaptive Ethernet interfaces	1, RJ-45 10/100/1000 Mbps self-adaptive Ethernet interface
PoE Interface	-	-	-	16 RJ-45 10/100 Mbps self-adaptive Ethernet interfaces
USB Interface	Voorzijde: 1 × USB 2.0; Achterzijde: 1 × USB 3.0	Voorzijde: 2 × USB 2.0; Achterzijde: 1 × USB 3.0	Voorzijde: 2 × USB 2.0; Achterzijde: 1 × USB 3.0	Voorzijde: 2 × USB 2.0; Achterzijde: 1 × USB 3.0



Switches

Artikelnummer	40790	40791	40792	40793
Model	TEG-S50G	DS-3E0505HP-E	DS-3E0318P-E	DS-3E0310HP-E
				
Aantal poorten	4	5	16	10
Netwerk Management Type	Unmanaged	Unmanaged	Unmanaged	Unmanaged
Primaire Poorten	4 x RJ45	3 x Gigabit PoE ports, 1 x Gigabit Hi-PoE port, and 1 x Gigabit RJ45 port	16 x 10/100 Mbps PoE ports, 2 x 10/100/1000 Mbps combo uplink ports	1 x 10/100 Mbps Hi-PoE-poort, 7 x 10/100 Mbps PoE-poorten en 2 x 10/100/1000 Mbps RJ45-poorten
Primaire Poorten snelheid	10/100/1000Mbps	10/100/1000Mbps	10/100/1000Mbps	10/100/1000Mbps
Switching Methode	Store en Forward	Store en Forward	Store en Forward	Store en Forward
Netwerk protocollen	TCP/IP	IEEE 802.3, IEEE 802.3u, IEEE 802.3x, and IEEE 802.3ab	IEEE802.3,802.3u,802.3x, 802.3af, 802.3at	IEEE 802.3, IEEE 802.3u, IEEE 802.3x, and IEEE 802.3ab
PoE	1 x PoE+, 3 x PoE poorten	1 x Gigabit Hi-PoE poort	16, 10/100Mbps RJ45 poorten	1 x 10/100 Mbps Hi-PoE poort

Harddisks

Artikelnummer	40720	40730	40740
Model	WD20PURX2TB	WD40PURX4TB	WD40PURX6TB
			
Opslagcapaciteit	2TB	4TB	6TB
Formaat	3.5 inch	3.5 inch	3.5 inch
Interfaces	SATA III	SATA III	SATA III
Toerental	5400omw/min	5400omw/min	5400omw/min
Cache	64MB	64MB	64MB